


	<p><b>Schaltplan Wiring diagram</b></p>	<p><b>USB 3.1 SuperSpeed+ Kabel USB C</b>  <b>Anschlüsse:</b> 2x USB-C-Stecker  <b>Materialien:</b>  <b>Isolierung:</b> PVC; schwarz  <b>Kontakte:</b> vergoldet  <b>Stecker:</b> vernickelt  <b>Innenleiter:</b> verzinnnes Kupfer  <b>Kabelaufbau:</b> [34AWG*1C+SP+AL/MY]+8COAX+  34AWG*1P+  34AWG*3C+  28AWG*2C+AL/MY+  B (85 %TC)  <b>Datenrate:</b> max. 5 Gbit/s; Generation 1  <b>USB-Standard:</b> 3.1  <b>Nennstromstärke:</b> 3 A  <b>Konformität:</b> RoHS</p>	<p><b>USB 3.1 SuperSpeed+ cable USB C</b>  <b>Connectors:</b> 2x USB-C plug  <b>Materials:</b>  <b>Insulation:</b> PVC; black  <b>Contacts:</b> gold-plated  <b>Plugs:</b> nickel-plated  <b>Inner conductor:</b> TC  <b>Cable constructin:</b> [34AWG*1C+SP+AL/MY]+8COAX+  34AWG*1P+  34AWG*3C+  28AWG*2C+AL/MY+  B (85 %TC)  <b>Data rate:</b> max. 5 Gbit/s; Generation 1  <b>USB standard:</b> 3.1  <b>Nominal current:</b> 3 A  <b>Conformity:</b> RoHS</p>
--	---	--	--

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.:	tf	<b>679760 USB3.1 C Gen.1 Kabel, 2x Typ C Stecker, schwarz - Länge: 1m</b> 	
02.03.2018	tf	gepr.:	tf		
31.07.2019	ss	Norm:			
Änderungen vorbehalten / Subject to change				Zeichnungs-Nr.:	von